

BEAM COMMISSIONING OF SEPARATED FUNCTION RFQ ACCELERATOR

J.E.Chen K.Zhu[#] Y.R.Lu X.Q.Yan Z.Wang M.L.Kang S.L.Gao M.Zhang S.X.Peng Z.Y.Guo
J.F.Guo W.G.Li J.X.Fang Z.Z.Song J.X.Yu M.L.Yu

State Key Lab of Nuclear Physics and Technology, Peking University, Beijing, China

Abstract

The beam commissioning of Separated Function RFQ (SFRFQ) accelerator, which can gain high accelerating efficiency and enough focusing strength for low energy high current beam, is presented. In order to demonstrate the feasibilities of this novel accelerator, a prototype cavity was designed and constructed. The O^+ beam was accelerated from 1MeV to 1.6MeV by SFRFQ cavity. A triplet was constructed for the transverse beam matching between the 1MeV ISR-RFQ 1000 and SFRFQ. A capacitance frequency tuning system and RF phase shifter were used to keep SFRFQ cavity working at the same frequency of ISR RFQ at the right phase. The whole RFQ accelerator system and the preliminary beam test results are presented in this paper.

INTRODUCTION

The RFQ accelerators are widely used to accelerate low energy intense heavy ion and proton beams nowadays. The RFQ team at Peking University has been engaged in developing RFQ technology by the end of 1980s. Since then a 300keV heavy ion Integrated Split-ring Resonator RFQ (ISR RFQ-300) with the mini-vane electrodes was constructed and put into operation in 1994. Based on these experiences, A 1MeV heavy ion ISR-RFQ (Integral Split Ring RFQ) 1000 was completed and run successfully in 2000[1].

Although RFQ structure has many advantages in accelerating low energy beam, the accelerating efficiency of RFQ structure is rather limited, since a considerable fraction of RF voltage is used for transverse focusing. Furthermore the efficiency falls off as the fixed voltage will be applied to the increasing cell length. Comparatively, the drift tube structure has higher acceleration efficiency, which is why the idea of introducing accelerating gaps into RFQ is also attractive for some applications. For example, SP RFQ [2], RFD [3] as well as chain-like structure [4] which introduces the accelerating gaps into RFQ, were under investigation in Russia, USA and Japan. For the same reason, the Separated Function RFQ (SFRFQ) was proposed by the RFQ group of IHIP (Institute of Heavy Ion Physics) at Peking university [5], based on the experience of ISR-RFQ 1000. Preliminary results of electro-magnetic and beam dynamics calculation proved the possibly higher RF accelerating efficiency of SFRFQ structure [6].

In order to demonstrate the feasibilities of the SFRFQ structure, a code SFRFQCODEV1.0[7] was developed specially for cavity design and beam dynamics simulation and a prototype cavity was designed and constructed according to the simulation results. The prototype cavity will be verified as a post-accelerator for ISR-RFQ 1000 and accelerate O^+ beam with \sim mA peak current from 1MeV to 1.6MeV. A match section between 1MeV RFQ and SFRFQ is designed for the transverse beam emittance matching. Meanwhile to upgrade the beam current to mA for ISR RFQ-1000, a new designed ECR ion source for this accelerator has been developed in the last two years [8]. The whole system of accelerators and the beam test results of the system will be presented in the following sections.

SYSTEM OF ACCELERATORS

The RFQ accelerator complex, which is shown in figure 1, consists of ECR ion source, LEBT, 1MeV RFQ accelerator, a triplet matching section, SFRFQ and analyzing magnet.

The old penning ion source was replaced by an ECR ion source, which is made of permanent magnets working at 2.45GHz. The magnet can generate 90~100mT axial magnetic field in discharging chamber. Two electrodes are used for ions extraction. The pure O_2 is used as working gas for ion source.




Figure 1: Accelerator system composed by ISR-RFQ 1000 and SFRFQ.

LEBT includes two electric lenses and a faraday cup, which is shown in figure 2. The first lens is composed by two diaphragms and one tube, the diameter of which is 80mm. the second is of three tube type Einzel lens with 120mm diameter. Faraday cup is put behind two lenses near the RFQ entrance. In order to avoid unacceptable high current entering the RFQ, which may damage the RFQ electrode and deteriorates the vacuum, a diaphragm with 15mm diameter is put after faraday cup at the entrance of the RFQ. When ion source works at 1/6 duty

*Work supported by NSFC (10805003 , 10855001)
Zhukun@pku.edu.cn




Figure 6: RF system.

BEAM TEST

After the triplet and SFRFQ cavity are installed on the beam line, the beam test experiment is carried out. The first beam of $162\mu\text{A}$ is measured at exit of SFRFQ by faraday cup with 1/6 duty factor at 166Hz repetition frequency. After first beam is measured, many parameters are changed to optimize the output beam quality of SFRFQ. The voltages of extraction and electric lenses are changed to improve the input beam quality of ISR-RFQ 1000. The exciting currents of triplet are changed to find the best input beam parameter of SFRFQ. The voltage of phase shifter is very important for beam test, so the voltage is scanned in a wide range to find an optimized voltage. So far, the best beam test result is $250\mu\text{A}$ at exit of SFRFQ. The experiment condition is listed in table1.

The beam energy analysis is done with analysis magnet and the result is recorded with x-y recorder. It matches with simulation result with SFRFQCODEV1.0, the experiment result is shown in the figure7.

Table 1: The Experiment Condition

Experiment condition	First result	Best result
Duty factor	1/6	1/16
Repetition frequency	166Hz	166Hz
Vacuum of discharge chamber	$2.0 \times 10^{-4}\text{Pa}$	$2.4 \times 10^{-4}\text{Pa}$
Extraction voltage	22.5kV	25kV
Voltage of lens 1	16.7kV	16.7kV
Voltage of lens 2	19.5kV	19.5kV
Input power of RFQ	28kw	31kw
Vacuum of RFQ	$2.7 \times 10^{-4}\text{Pa}$	$2.2 \times 10^{-4}\text{Pa}$
Input power of SFRFQ	20kw	20kw
Vacuum of SFRFQ	$5.0 \times 10^{-4}\text{Pa}$	4.9×10^{-4}
Current of triplet magnet 1	65.0A	56.6A
Current of triplet magnet 2	47.5A	41.2A
Current of triplet magnet 3	65.0A	30.0A
Voltage of phase shifter	4.9V	3.4V
Working frequency	26.075MHz	26.074MHz




Figure 7: beam energy spectrum of experiment.

The beam current measured at faraday cup near the entrance of SFRFQ is about 3mA, while the inputted O^+ beam for the 1 MeV RFQ is $\sim 4\text{ mA}$. A large part of beam is lost in SFRFQ cavity. The main possible reason is: the beam spot at the entrance of SFRFQ cavity is 11mm in x direction and 17mm in y direction, so it is much bigger than ideal beam spot and exceeds the acceptance of SFRFQ cavity. Big beam spot might come from beam emittance considerable increment in the 1 MeV RFQ. The method to reduce the input beam emittance will be studied in the near future.

CONCLUSION

Beam test shows that the SFRFQ have high acceleration efficiency. The extraction voltage of ion source, voltage of electric lenses, the triplet current and the voltage of phase shifter effect the output beam of SFRFQ. Although the beam transmission in SFRFQ is low, the energy spectrum of SFRFQ is match well with simulation result. In experiment we find the main reason of the beam loss in SFRFQ and will improve it in the near future.

REFERENCE

- [1] Y.R.Lu, C.E.Chen, J.X.Fang, et al. NIMA, A515(2003):394-403
- [2] S.Minaev. Nuclear Instruments and Methods in Physics Research section A, 2002, 489(1-3): 45-58
- [3] D.A. Swenson, K.R. Crandall, F.W. Guy et al. First Performance of RFD Linac structure. In: Argonne National Laboratory. Proceedings of the 1998 LINAC Conference. Chicago: 1998. 648-650
- [4] M. Odera, M. Hemmi. Accelerating structure with chain-like electrode configuration. In: GSI. Proceedings of the 1984 LINAC Conference. Seeheim: 1984. 346-348
- [5] CHEN Jia-Er, FANG Jia-Xun, LI Wei-Guo et al. Progress on Natural Science, 2002, 12(1): 23-28(in Chinese)
- [6] YAN Xue-Qing, CHEN Jia-Er, FANG Jia-Xun et al. Nuclear Instruments and Methods in Physics Research section A, 2003, 506(1): 1-6
- [7] Z. Wang, et al, Nuclear Instruments and Methods in Physics Research, A, 572, 2007, 596-600
- [8] PENG Shi-Xiang, SONG Zhi-Zhong, QIAN Feng et al. High Energy Physics And Nuclear Physics, 2007, 31(S1): 63-65
- [9] Z.Wang, Peking university dissertation, 2008