

LONGITUDINAL AND TRANSVERSE T AND S TRANSIT TIME COEFFICIENTS

B. Schnizer^{*})

European Organization for Nuclear Research
Geneva, Switzerland

Summary

Difference equations describing the motion of a proton through an accelerating gap have been given by P. Lapostolle at the Frascati Conference (1965) and by the author (Washington Conference, 1967). The dynamical coefficients contained in them are discussed here. There are two types, called T- and S-coefficients. T-coefficients belong to motion across the whole gap and have a simple form (transit time factor times a modified Bessel function). Difference equations through the first half of the gap needed to determine the mid-gap values of the particle coordinates, involve in addition S-coefficients. Exact expressions (series expansions) for the latter are given here assuming that the Fourier coefficients of $E_z(r=a)$, the longitudinal field along the gap circumference, are known. Approximations for the S-coefficients are discussed. Corrected Tables of non-relativistic and relativistic difference equations are given.

1. Introduction

At the Frascati Conference P. Lapostolle¹⁾ gave a set of difference equations which correct and extend the so-called Panofsky equations²⁾ describing the phase change and energy gain along a linear accelerator. In this new version transverse motion too was taken into account. A new and improved derivation (including relativistic effects) was given by the author³⁾. The difference equations for the change of kinetic energy, phase, radial slope and position across the whole gap involve only T-coefficients which essentially consist of the transit time factor times a Bessel function. However, these still depend upon the unknown mid-gap values of the particle coordinates. For the determination of the latter difference equations for the first half of the gap must be used. These contain besides the T-coefficients S-coefficients which are of a more intricate nature. The expressions for all these coefficients are given here and approximations for them are discussed. The

method how to derive this difference equation is described elsewhere³⁾⁴⁾⁵⁾. Only corrected versions of the difference equations are listed in Tables III to VI.

2. Field Representations

The field in the accelerating gap is supposed to be an axially symmetrical time-harmonic TM-field (angular frequency ω) whose component E_z is symmetrical about $z = 0$, the centre of the gap.

$$\begin{aligned} E_{z,r}(z,r,\varphi) &= E_{z,r}(z,r) \cos(\varphi + \varphi_0) \\ E_z(z,r) &= E_z(-z,r) \quad E_r(z,r) = -E_r(-z,r) \\ H_\theta(z,r,\varphi) &= H_\theta(z,r) \sin(\varphi + \varphi_0) \\ H_\theta(-z,r) &= H_\theta(z,r) \end{aligned} \tag{1}$$

$\varphi = \omega t$ is time-angle (= phase). Field components are expressed by Fourier-integrals:

$$\begin{aligned} E_z(z,r) &= \frac{E_1}{2\pi} \int_{-\infty}^{\infty} \frac{b(k_z)}{J_0(\gamma a)} J_0(\gamma r) e^{ik_z z} dk_z \\ E_r(z,r) &= -i \frac{E_1}{2\pi} \int_{-\infty}^{\infty} b(k_z) \frac{k_z J_1(\gamma r)}{\gamma J_0(\gamma a)} e^{ik_z z} dk_z \\ \mu H_\theta(z,r) &= -\frac{E_1}{2\pi} \frac{k_0}{c} \int_{-\infty}^{\infty} b(k_z) \frac{J_1(\gamma r)}{\gamma J_0(\gamma a)} e^{ik_z z} dk_z \end{aligned} \tag{2}$$

with

$$\gamma = \gamma_1 + i\gamma_2 = ik_r = (k_0^2 - k_z^2)^{1/2} \quad \gamma_2 \geq 0$$

a is the inner radius of the drift tube. The amplitude function $b(k_z)$ can be related to field $E_z(z, a)$ applied along the gap ($r = a$, $|z| \leq p/2$):

$$E_z(z, a) = E_1 \sum_{s=0}^{\infty} B_s \cos(2\pi s z/p) \quad (3)$$

$$b(k_z) = 2 \sum_{s=0}^{\infty} B_s (-1)^s \sin(k_z p/2) (k_z - 2\pi s/p)^{-1} \quad (4)$$

($B_0 = 1$, $B_s = B_{-s}$) by a Green's function for a wave guide. $p = g + 2R_i$ where g is the gap length (= minimum distance between drift tubes) and R_i is the radius of curvature of the inner drift tube rim. The instantaneous peak "voltage" (at $\varphi = -\varphi_0$) along the line $r = \text{const.}$ is:

$$V(r) = \int_{-\infty}^{\infty} E_z(z, r) dz = V_0 J_0(k_0 r) \\ = E_1 b(0) J_0(k_0 r) / J_0(k_0 a) \quad (5)$$

($b(0) = p$). $V(a) = E_1 p$, $V_0 = V(0) = E_1 p / J_0(k_0 a)$. E_1 is the average field strength across the gap, V_0 is the voltage along the axis (of one cell). Evaluation of the integral representations (2) with the amplitude function (4) gives series expansions of the field. These still contain the unknown Fourier coefficients E_1 , B_s . A finite number of them may be extracted from cavity fields calculated by numerical methods (mesh calculations⁵) which usually give numerical values for $U = -rH_\theta(z, r)$. The series for $U = -rH(z, r)$ (Table I) is used for $r = a$ to set up a system of n equations of n Fourier-coefficients (n is the number of mesh points within the gap where values of U are given).

3. Beam Dynamics Coefficients

Beam dynamics coefficients are Fourier transforms (in z) of the field components. There are two types of them, T- and S-coefficients. T-coefficients are integrals over across the whole interval ($-\infty \leq z \leq \infty$). They appear in difference equations where the particle crosses the whole gap cell (or gap). Their expressions are simple. The S-coefficients are defined as integrals over $0 \leq z \leq \infty$ and are needed in difference equations along half of the cell. Their expressions are complicated.

The longitudinal, transverse and magnetic T-coefficient are defined as:

$$V_0^T(k, r) \equiv \int_{-\infty}^{\infty} E_z(z, r) \cos(kz) dz = \\ V_0^T(k) I_0(k_r r) \\ V_0^T(k, r) \equiv \int_{-\infty}^{\infty} E_r(z, r) \sin(kz) dz = \\ V_0^T(k) k I_1(k_r r) / k_r \quad (6) \\ V_0^T(k, r) \equiv - \int_{-\infty}^{\infty} \frac{c}{k_0} \mu H_\theta(z, r) \cos(kz) dz = \\ V_0^T(k) I_1(k_r r) / k_r$$

with

$$k_r = (k^2 - k_0^2)^{1/2} \quad (7)$$

They are known as soon as the transit time factor:

$$T_0(k) \equiv \int_{-\infty}^{\infty} E_z(z, 0) \cos(kz) dz = \\ (b(k)/b(0)) \times J_0(k_0 a) / I_0(k_r a) \quad (8)$$

is given and are nothing more than convenient abbreviations. $T_0(k)$ is a measure of the distribution of E_z in the longitudinal direction. $T_0(k)^2$, its derivatives $T_0'(k)$, $T_0''(k)$ (and the above T-coefficients) are needed for the single value $k = \omega/\dot{z}_0$ ($\dot{z}_0 =$ longitudinal velocity of the particle at the gap centre). They may be easily obtained from fields given numerically by numerical integration of the integral defined in (8) (and from the formulae (6)). If the cell is regarded as a closed cavity, the limits of integration $+\infty$ in (6), (8) and (9) must be replaced by $+L/2$ (L is cell length) and k by $2\pi/L$. This hardly changes the numerical values of these quantities. This method may be more convenient than to express $T_0(k)$ by the Fourier coefficients B_n introduced in Chapter 2:

$$T_0(k) = T_{00}(k) (1 + Y) \\ T_{00}(k) = \frac{J_0(k_0 a)}{I_0(k_r a)} \frac{\sin(kp/2)}{(kp/2)} \quad (8a) \\ Y = - \sum_{n=1}^{\infty} \frac{2(-1)^n B_n(kp)^2}{(2\pi n)^2 - (kp)^2}$$

The longitudinal, transverse and magnetic S-coefficient are defined as:

$$\begin{aligned}
 V_0 S_1(k,r) &= 2 \int_{-\infty}^{\infty} E_z(z,r) \sin(kz) dz \\
 V_0 S_r(k,r) &= 2 \int_{-\infty}^{\infty} E_r(z,r) \cos(kr) dz \\
 V_0 S_m(k,r) &= -\frac{2c}{k_0} \int_0^{\infty} \mu H_\theta(z,r) \sin(kz) dz
 \end{aligned} \tag{9}$$

S_1 and S_r (as well as T_1 and T_r) are dimensionless while S_m (and T_m) have the dimension of a length. This may be inconvenient in numerics: T_1, T_r, S_1, S_r are somewhat smaller than unity, S_m and T_m are smaller than these by a factor 10 to 100. Defining kT_1 and kS_m in place of the expressions given in (6) and (8) brings disadvantages for the writing of difference equations. For numerical work it is suggested to normalize T_1 and S_m by multiplying them by $2\pi/L$ and to modify dynamical formulae in Tables V and VI accordingly. In all these formulae S_m (or $dS_m/dk, d^2S_m/dk^2$) is preceded by k , so the normalization can be done in the following manner $kS_m = (kL/2\pi) \times (2\pi S_m/L) = (kL/2\pi) \times S_m$ norm, $kL/2\pi \approx 1$.

The S-coefficients are related to each other by the following equations:

$$\begin{aligned}
 V_0 \partial S_1(k,r)/\partial r &= 2\omega\mu H_\theta(0,r)/k - \\
 &\quad - V_0 k_r^2 S_r(k,r)/k \\
 V_0 \partial S_r(k,r)/\partial r &= 2 E_z(0,r) - \\
 &\quad - V_0 S_r(k,r)/r - k V_0 S_1(k,r)
 \end{aligned} \tag{10}$$

$$V_0 S_m(k,r) = \frac{2c}{k k_0} \mu H_\theta(0,r) - \frac{1}{k} V_0 S_r(k,r)$$

These probably will not be exactly valid, if the limits of integration in (8) are $\pm L/2$, but may represent a good approximation. They could be useful for the calculation of radial derivatives of S-coefficients since they permit to circumvent the need of radial derivatives of the field components. With the help of series (4) for $b(k_z)$, series expansions of the S-coefficients may be found. They are listed in Table II. Unfortunately they are complicated. S_1 and S_r are more important than S_m which only appears in relativistic formulae where the need for the half gap difference equations is less severe.

Fourier coefficients B_n and thereafter $S_n(k,r)$, $S_1(k,r)$ (with $k = \omega/z_0$), $0 \leq r \leq a$, have been calculated from the potentials $U = -rH_\theta$ of various Alvarez cavities (0.6 - 8 MeV). There emerge the following results:

a) S_1 may be approximated by the first two terms and by the first (eventually second) term of the simple series in n . The contribution of the double series is negligible. The first term is small at low energy, appreciable at higher energies. This can be explained as follows: $kg/2 \approx \pi/2$. In low energy cavities $kp/2 = k(g/2 + R_1)$ comes near to π and the cotangent is small, while at higher energies R_1 is small compared with g and $kp/2$ is nearer to $\pi/2$ and the cotangent is larger. The term proportional to $J_0(kr)$ is the most important one, it is always greater than $S_1(k,r)$; it is almost constant with r . The terms with $n = 1$ (2) contribute 30% (1%) at .6 MeV, 10% (2%) at 8 MeV at $r = a$, for smaller r the situation is better. Therefore at low energy the formula for S_1 derived for homogeneous field $E_z(z,a) = E_1$ ($|z| \leq p/2$) appears not a very good approximation. S_1 decreases slightly with increasing energy.

b) S_r may be approximated by the single term and by the first two (eventually three) terms of the series in n while the double series can be neglected. The absolute value of the term with $n = 1$ (2, the rest of the sum) contribute 110%, (10%, 2%) of S_r at 0.6 MeV, 50% (25%, 37%) of S_r at 8 MeV. At higher energy terms with greater n become important, but the error introduced by their neglect is less harmful since in the difference equations the S_n are multiplied by $eV_0/2W$ and the kinetic energy W increases.

Derivatives of S-coefficients are under investigation and results will be given in ref.5).

4. Difference Equations

Tables III to VI contain difference equations for particle dynamics in an accelerating gap. They have been slightly corrected in comparison with those published earlier⁵⁾. Increments as needed in the thin lens approximation are listed, e.g. $\Delta\bar{\varphi} = \Delta(\varphi - z d\varphi/dz)$, $\Delta(r - z dr/dz) = \Delta\bar{r}$. For example, the trajectory of the entering non-relativistic (relativistic) particle is extended for free motion up to the centre; there is the thin lens, the coordinates are incremented by $\Delta W, \Delta\bar{\varphi}, \Delta r', \Delta\bar{r}$ of Table III (Table IV) and then sets in free motion with these new values. The difference equations of these Tables (III and IV) contain the still unknown mid-gap values W, φ, r', r_0 . The difference equations of Table V and VI for the motion through the first half of the gap may be used to determine them. As a matter of experience, the corrections involving S-coefficients become less and less important with increasing particle energy.

All these difference equations have been found by first order perturbation theory as described elsewhere³⁾⁴⁾⁵⁾. The action of the gap field on the otherwise freely moving particle is treated as a perturbation. Solutions of the equations of motion are expanded into powers of $\mathcal{E} = eV_1 / (m\omega p_0^z)$ (= impact of the field during one period/free particle momentum) and terms linear in \mathcal{E} lead to the difference equations. In the non-relativistic equation only the electrical field has been retained. In the relativistic treatment are considered the magnetic field and the mass variation too. The integral representations (2) of the field are inserted into the first order equations and z and r in $eE_z(z, r, \varphi)$ equal the zero order solution $\varphi^{(0)} = \varphi/k_z$ and $r^{(0)} = \dot{r}_0 \varphi/\omega + r_0$. The equations of motion can then be solved by quadratures. Afterwards the integrals in k_z are evaluated by Cauchy's residue theorem. For integrals across the whole gap there are only dynamical poles at $k_z = \pm k$ (poles at $J_0(a\gamma) = 0$ corresponding to the evanescent wave guide modes can be neglected) rendering the terms in Tables III and IV. They cut out from the continuous spectrum of waves in (2) the partial waves whose phase velocity equals the particle velocity. For the half gap difference equations the trajectory ends at the gap centre. In the k_z -plane appear additional poles at $k_z = \pm 2\pi n/p$, $n = 0, 1, 2, \dots$. They describe standing waves as they exist within the gap and yield the simple series in n contained in the S-coefficients.

Acknowledgements

The author is very indebted to Dr. P.M. Lapostolle for suggesting this topic and many helpful discussions. Dr. A. Katz, Saclay, Drs. M. Martini and D.J. Warner, CERN, provided the results of their cavity calculations. The programmes have been prepared by Mme Y. Marti.

References

1. A. Carne, P.M. Lapostolle, P. Promé,
Proc. 5th Int. Conf. High Energy Acc.,
Frascati, 1965, 656-662.
2. W.H.K. Panofsky,
UCRL-1216.
3. B. Schnizer,
Proc. U.S. National Particle Acc. Conf.,
Washington 1967, IEEE Trans. Nuclear
Science, NS-14, 557-561 (1967).

4. Linear Accelerators, Ed. P.M. Lapostolle
and A. Septier, North Holland Publ. Co.,
Chap. C.1.2.b (by A. Carne et al.)
(in preparation).
5. B. Schnizer,
General Properties of Fields and Beam
Dynamics in an Accelerating Gap
(to appear as a yellow CERN report).
6. M. Martini, D.J. Warner,
CERN 68-11; ref. 4), Chapter C.1.1d
(A. Katz).
7. A. Carne and P.M. Lapostolle,
Proc. 1966 Linear Acc. Conf., Los Alamos,
LA-3609, 201-204.

*) On leave from Institut für Theoretische
Physik, Technische Hochschule, Graz,
Austria.

Table I - Series Expansion of the Gap Field

$$|z| \leq p/2 : \quad U(z, r) = -r H_0(z, r) = 2 E_1 \epsilon \omega r p \times$$

$$\times \left[\frac{2}{k_0 p} \frac{J_1(k_0 r)}{J_0(k_0 a)} + \sum_{n=1}^{\infty} B_n \cos(2\pi n \frac{z}{p}) \frac{1}{\mu_n} \frac{I_1(\mu_n r/p)}{I_0(\mu_n a/p)} - 2 \frac{p}{a} \sum_{n=0}^{\infty} \frac{B_n (-1)^n}{1 + \delta_{no}} \sum_{\nu=1}^{\infty} \frac{J_1(j_\nu r/a) \cosh(\eta_\nu z) e^{-\eta_\nu p/2}}{J_1(j_\nu)} \frac{1}{(p \eta_\nu)^2 + (2\pi n)^2} \right]$$

$$E_z(z, r) = (\epsilon \omega r)^{-1} \partial U(z, r) / \partial z \quad E_r(z, r) = -(\epsilon \omega r)^{-1} \partial U(z, r) / \partial r$$

Table II - Expressions for T- and S-coefficients

$$T_1(k, r) = T_0(k) I_1(k_r r) \quad T_m(k, r) = T_0(k) I_1(k_r r) / k_r$$

$$T_r(k, r) = T_0(k) k I_1(k_r r) / k_r \quad k_r = (k^2 - k_0^2)^{1/2}$$

$$S_1(k, r) = -\text{ctg}(kp/2) T_0 I_0(k_r r) + \frac{J_0(k_0 r)}{pk/2} - 4 J_0(k_0 a) \sum_{n=1}^{\infty} \frac{pk B_n}{(2\pi n)^2 - (kp)^2} \frac{I_0(\mu_n r/p)}{I_0(\mu_n a/p)}$$

$$- 8 J_0(k_0 a) (kp) \left(\frac{p}{a}\right)^2 \sum_{n=1}^{\infty} \frac{B_n (-1)^n}{1 + \delta_{no}} \sum_{\nu=1}^{\infty} \frac{J_0(j_\nu r/a)}{J_1(j_\nu)} \frac{\exp(-\eta_\nu p/2)}{(kp)^2 + (\eta_\nu p)^2} \frac{j_\nu}{(2\pi n)^2 + (\eta_\nu p)^2}$$

$$S_r(k, r) = \text{ctg}(kp/2) T_0(k) k I_1(k_r r) / k_r + 4 J_0(k_0 a) \sum_{n=1}^{\infty} \frac{B_n (2\pi n)^2}{(2\pi n)^2 - (kp)^2} \frac{1}{\mu_n} \frac{I_1(\mu_n r/p)}{I_0(\mu_n a/p)}$$

$$- 8 J_0(k_0 a) \frac{p}{a} \sum_{n=1}^{\infty} \frac{B_n (-1)^n}{1 + \delta_{no}} \sum_{\nu=1}^{\infty} \frac{J_1(j_\nu r/a)}{J_1(j_\nu)} \frac{\exp(-\eta_\nu p/2)}{(kp)^2 + (\eta_\nu p)^2} \frac{(\eta_\nu p)^2}{(kp)^2 + (\eta_\nu p)^2}$$

$$\frac{1}{p} S_m(k, r) = -\text{ctg}(kp/2) T_0(k) \frac{1}{k_r p} I_1(k_r r) + \frac{2}{kp} \frac{J_0(k_0 r)}{k_0 p} - 4 J_0(k_0 a) kp \sum_{n=1}^{\infty} \frac{B_n}{(2\pi n)^2 - (kp)^2} \frac{1}{\mu_n} \frac{I_1(\mu_n r/p)}{I_0(\mu_n a/p)}$$

$$- 8 J_0(k_0 a) kp \frac{p}{a} \sum_{n=1}^{\infty} \frac{B_n (-1)^n}{1 + \delta_{no}} \sum_{\nu=1}^{\infty} \frac{J_1(j_\nu r/a)}{J_1(j_\nu)} \frac{\exp(-\eta_\nu p/2)}{(kp)^2 + (\eta_\nu p)^2} \frac{1}{(2\pi n)^2 + (\eta_\nu p)^2}$$

$$\mu_n = \left[(2\pi n)^2 - (k_0 p)^2 \right]^{1/2}$$

Table III - Nonrelativistic change of longitudinal kinetic energy, reduced phase, radial slope and reduced radial position across a gap

$$\begin{aligned}
 \Delta W &= eV_0 \quad T_0 I_0 \quad \cos\phi + eV_0 \quad d/dk(T_0 k_r I_1) \quad r' \sin\phi \\
 \Delta \bar{\phi} &= \alpha k \quad d/dk(T_0 I_0) \quad \sin\phi - \alpha k \quad d^2/dk^2(T_0 k_r I_1) \quad r' \cos\phi \\
 \Delta r_r' &= -\alpha \quad (T_0 k I_1 / k_r) \quad \sin\phi + \alpha \left[d/dk(T_0 k I_1') - T_0 I_0 \right] \quad r' \cos\phi \\
 \Delta \bar{r} &= -\alpha \quad d/dk(T_0 k I_1 / k_r) \quad \cos\phi - \alpha \left[d^2/dk^2(T_0 k I_1') - d/dk(T_0 I_0) \right] \quad r' \sin\phi
 \end{aligned}$$

Table IV - Change of the Same Quantities in the Relativistic Case

$$\begin{aligned}
 \Delta W_r &= \Delta W \quad \left[-eV_0 \quad (T_0 k I_1 / k_r) \quad r' \sin\phi \right]^* \\
 \Delta \bar{\phi}_r / (1 - \beta_0^2)^{1/2} &= \Delta \bar{\phi} \quad (1 - k_0^2/k^2) \quad - \alpha k \quad (k_0^2/k^2) \quad (T_0 I_1 / k_r) \quad r' \cos\phi \\
 \Delta r_r' / (1 - \beta_0^2)^{1/2} &= \Delta r_r' \quad (1 - k_0^2/k^2) \quad + \alpha \quad (k_0^2/k^2) \quad T_0 \quad (I_1' - I_0) \quad r' \cos\phi \\
 \Delta \bar{r}_r / (1 - \beta_0^2)^{1/2} &= \Delta \bar{r} \quad (1 - k_0^2/k^2) - \alpha \quad (k_0^2/k^2) \quad (T_0 I_1 / k_r) \quad \cos\phi - \alpha \quad (k_0^2/k^2) \quad d/dk(2T_0 I_1' - T_0 I_0) \quad r' \sin\phi
 \end{aligned}$$

* Adding the term in the square brackets gives the gain in total kinetic energy.

Table V - Change of Kinetic Energy, Reduced Phase, Radial Slope and Reduced Radial Position along the First Half of the Gap

$$\begin{aligned}
 \Delta w_1 &= \Delta W/2 + (eV_0/2) \left[S_1 \quad \sin\phi - \quad d/dk \quad \partial S_1 / \partial r \quad r' \cos\phi \right] \\
 \Delta \bar{\phi}_1 &= \Delta \bar{\phi}/2 - (\alpha k/2) \left[dS_1/dk \quad \cos\phi + \quad d^2/dk^2 \quad \partial S_1 / \partial r \quad r' \sin\phi \right] \\
 \Delta r_1' &= \Delta r_r'/2 - (\alpha/2) \left[S_r \quad \cos\phi + \quad (d/dk \quad \partial S_r / \partial r + S_1) \quad r' \sin\phi \right] \\
 \Delta \bar{r}_1 &= \Delta \bar{r}/2 + (\alpha/2) \left[dS_r/dk \quad \sin\phi - \quad (d^2/dk^2 \quad \partial S_r / \partial r + dS_1/dk) \quad r' \cos\phi \right]
 \end{aligned}$$

Table VI - Change of the Same Quantities in the Relativistic Case

$$\begin{aligned}
 \Delta w_{r1} &= \Delta W_r/2 + (eV_0/2) \left\{ S_1 \sin\varphi - \left(\frac{\partial}{\partial r} \frac{dS_1}{dk} \left[- S_r \right]^* \right) r' \cos\varphi \right\} \\
 &= \Delta w_1 + r \left[- T_r \sin\varphi - S_r \cos\varphi \right]^* \\
 \Delta \bar{\varphi}_{r1} &= \Delta \bar{\varphi}_r/2 - (1 - \beta_0^2)^{1/2} \frac{\alpha k}{2} \left\{ \left(1 - \frac{k_0^2}{k^2} \right) \left(\frac{dS_1}{dk} \cos\varphi + \frac{\partial}{\partial r} \frac{d^2 S_1}{dk^2} r' \sin\varphi \right) - \frac{k_0^2}{k^2} \left(\frac{dS_r}{dk} + k \frac{dS_m}{dk} \right) r' \sin\varphi \right\} \\
 &= (1 - \beta_0^2)^{1/2} \left\{ \left(1 - \frac{k_0^2}{k^2} \right) \Delta \bar{\varphi}_1 - \frac{k_0^2}{k^2} \frac{\alpha k}{2} r' \left(\frac{T_0 I}{k_r} \cos\varphi - \left[\frac{dS_r}{dk} + k \frac{dS_m}{dk} \right] r' \sin\varphi \right) \right\} \\
 \Delta r'_{r1} &= \Delta r'_r/2 - (1 - \beta_0^2)^{1/2} \frac{\alpha}{2} \left\{ \left(S_r + \frac{k_0^2}{k^2} k S_m \right) \cos\varphi + \left(\frac{\partial}{\partial r} \left[\frac{dS_r}{dk} + \frac{k_0^2}{k^2} k \frac{dS_m}{dk} \right] + S_1 \right) r' \sin\varphi \right\} \\
 \Delta \bar{r}'_{r1} &= \Delta \bar{r}'_r/2 + (1 - \beta_0^2)^{1/2} \frac{\alpha}{2} \left\{ \left(\frac{dS_r}{dk} + \frac{k_0^2}{k^2} k \frac{dS_m}{dk} \right) \sin\varphi - \left(\frac{\partial}{\partial r} \left[\frac{d^2 S_r}{dk^2} + \frac{k_0^2}{k^2} k \frac{d^2 S_m}{dk^2} \right] + \frac{dS_1}{dk} \right) r' \cos\varphi \right\}
 \end{aligned}$$

* Adding the term in the square bracket gives the gain in total kinetic energy.

Common to Tables III to VI

$$\begin{aligned}
 \alpha &= eV_0/(2W) & k_0^2/k^2 &= (dz/dt)_0^2/c^2 \approx \beta_0^2 \\
 W &= m/2 (dz/dt)_0^2 = (m/2) \dot{z}_0^2 \quad m = \text{rest mass} & - k_0^2/k^2 &= k_r^2/k^2 \approx 1 - \beta_0^2
 \end{aligned}$$

The argument $k = \omega/\dot{z}_0$ of $T_0(k)$, $k_r r_0$ of the modified Bessel functions $I_n(k_r r)$ and k, r_0 of $S_1(k, r_0)$, $S_r(k, r_0)$, $S_m(k, r_0)$ and the subscript $_0$ of φ_0 , r_0 and $r'_0 = (dr/dz)_0$ have been dropped. In all the expressions of Tables III to VI all these parameters refer to mid-gap values.