

# COMMISSIONING OF $e^+/e^-$ TRANSFER LINE FROM BINP INJECTION COMPLEX TO VEPP-2000 FACILITY\*

I.M. Zemlyansky<sup>#</sup>, Yu.S. Aktershev, V.V. Anashin, A.V. Andrianov, A.M. Batrakov, O.V. Belikov, D.E. Berkaev, M.F. Blinov, B.A. Dovzhenko, F.A. Emanov, V.V. Gambaryan, V.A. Kiselev, I.A. Koop, I.A. Mikheev, D.A. Nikiforov, A.V. Otboev, V.P. Prosvetov, V.V. Rashchenko, A.M. Semenov, P.Yu. Shatunov, Y.M. Shatunov, S.S. Vasichev, V.D. Yudin, Yu.M. Zharinov, BINP SB RAS, Novosibirsk, Russia  
 A.A. Krasnov, A.V. Pavlenko, Y.A. Rogovsky, D.B. Shwartz, A.A. Starostenko, BINP SB RAS, Novosibirsk; NSU, Novosibirsk, Russia

## Abstract

VEPP-2000  $e^+/e^-$  collider [1] was constructed in 2006 at BINP. The design luminosity of  $1 \times 10^{32} \text{ cm}^{-2} \text{ s}^{-1}$  may be achieved at filling rate of  $1 \times 10^8 e^+/e^-$  per second. Old VEPP-2M facility infrastructure provided only  $1 \times 10^7 e^+/e^-$  per second. We decided to use Injection Complex [2, 3]. The transfer line [4] connects Injection Complex and VEPP-2000 facility. Commissioning of  $e^+/e^-$  transfer line from Injection Complex to VEPP-2000 facility is done in 2016. Both electrons and positrons beams are injected to VEPP-2000 collider.

## GEOMETRY AND OPTICS

We simulated the optics with the RING program [5]. Detailed geometry and optics are shown in Figures 1-9.




Figure 1: The transfer line location.




Figure 2: The descent from the storage ring.




Figure 3: Lattice functions of the descent.

\*The work is supported by the Ministry of Education and Science of the Russian Federation, NSh-10088.2016.2

<sup>#</sup>I.M.Zemlyansky@inp.nsk.su



Figure 4: First horizontal bend.




Figure 5: Lattice functions of first horizontal bend.




Figure 6: Second horizontal bend.




Figure 7: Lattice functions of second horizontal bend.




Figure 8: The ascent to booster BEP.




Figure 9: Lattice functions of the ascent.

### MAGNETS AND POWER SUPPLIES

We calculated magnets with the aid of the MERMAID code [6]. Parameters of magnets and power supplies [7] are listed in Table 1.

Table 1: Magnetic elements and power supplies for beam energy of 510 MeV.

Element	Parameters	Power supply
6 dipoles of the descent	H=1.52T L=0.88m	2 DC, IST I=1.1kA
2 horizontal dipoles of the first bend	H=0.08T L=1.51m	1 DC, UM-20, I=20A
2 horizontal dipoles of the second bend	H=0.1T L=0.51m	1 DC, UM-20, I=20A
4 vertical dipoles of the ascent to the booster BEP	H=0.67T L=1m	1 AC, GID-3000, W=3kJ
1 horizontal dipole before the septum of BEP	H=1.74T L=0.29m	1 AC W=2.4kJ
1 septum of BEP	H=1.74T L=0.43m	1 AC W=2.4kJ
18 quadrupoles of the descent, the ascent and the matching part	G=1-16T/m L=0.2m	18 AC, GID-25, W=25J
43 quadrupoles of the regular part	G=2.59T/m L=0.2m	8 AC, GID-25, W=25J
6 dipole correctors in 6 dipoles of the descent	Hmax=0.02T L=0.88m	6 DC, PS-3A, I=3A
11 dipole correctors in 11 quadrupoles of the descent and the ascent	Hmax=0.1T L=0.2m	11 AC, GID-25, W=25J
27 dipole correctors	Hmax=0.01T L=0.1m	27 DC, PS-3A, I=3A

### VACUUM SYSTEM

The vacuum chambers are made of stainless steel. The inner aperture of quadrupoles is 23 mm. Inner regular part dipole's aperture is 24 mm, inner descent and ascend dipole's aperture is 21 mm. The required vacuum level of  $1 \times 10^{-8}$  Torr was obtained by sputter ion pumps (quantity is 8 pcs) with pumping speed of 160 l/s (nitrogen equivalent). We located pumps at the distance of 25 meters each other.

### CONTROL SYSTEM

We based the automation system [8, 9] on several PC platforms under Linux operating system. The control of power supplies is based on VsDC2 integrators [10, 11].

Some fragments of control software are shown in Figure 10-14.

6KX4	2850	2830	3.39	6M1	-23	-23	-0.07
6KZ5	-1000	-998	-1.13	6M2	-1170	-1167	-3.57
6KX6	-800	-798	-0.96	6M3	365	364	1.11
6KZ7	2500	2492	3.27	6M4	-2975	-2966	-9.43

Figure 10: Control of some DC-elements.

Name	DAC	GV1	Mask	Biip	ADCO	ADC1	3iipStart	3iipMask	RegIn	Allow
1 6L-51	-1.650	550	1	-23.180	-1.648	-1.650	1050	1	0	1
2 6L-52	-1.450	550	1	-20.374	-0.681	-1.449	1050	1	0	1
3 6L-53	1.650	550	1	36.361	1.466	1.648	1050	1	0	1
4 6L-54	1.400	558	1	30.502	1.400	1.400	1050	1	0	1
5 6KZL-25	1.700	0	0	-0.003	1.702	-9.445	1110	1	0	1
6 6KXL-26	0.600	610	1	8.203	0.259	0.603	1110	1	0	1
7 6M9	4.690	6500	1	-39.169	4.578	4.549	2800	1	0	1

Figure 11: Control of some AC-elements.

6KZL-27	-3.5	6L-55	3.9	6KXL-28	-2.7	6L-56	-0.3
1068.4	2355.3	776.1	-0.1				
6KXL-29	-3.0	6L-57	2.6	6KZL-30	-0.4	6L-58	-0.1
-778.3	6044.1	778.1	3977.9				
6M9-12							
6M9-12.1			-0.6	6M9-12.2			-0.7
15280.6			22159.7				

Figure 12: Control of some power supplies.




Figure 13: Image current monitors over the transfer line.




Figure 14: Current distribution over the transfer line.

### BEAM DIAGNOSTICS

We used three types of sensors for beam diagnostics: 12 luminophor probes, 24 image current monitors and 1 Faraday cup. They are presented in Figures 15-17.




Figure 15: We used image current monitors in real time beam pass.




Figure 16: Luminophor probes are used for first beam-pass. Beam-picture's size is about 20 mm.




Figure 17: We use Faraday cup to determine the number of particles in the beam before the ascent. The graph shows the beam discharge.

## CONCLUSION

During creation of the transfer line, a number of tasks has been solved. We created the optical scheme of the transfer line connecting Injection Complex and VEPP-2000 facility. Simulation of the acceptance of BEP [12] in the admission place for determination of optimum coordinates and inclinations of bunches is carried out. We simulated magnetic calculations of all magnetic elements, beginning from the descent. We made the analysis of possible deviations of the bunch trajectory from a design trajectory, for the reasons of instability of power supplies and possible errors of a geodetic exhibition. For correction of a trajectory, installation sites of dipole correctors are optimized. Considering an arrangement of magnetic elements and dipole correctors, we defined locations of the diagnostic equipment. Losses of positrons and electrons at design luminosity of a collider of VEPP-2000 are estimated. Proceeding from the necessary speed of replenishment of particles, we developed the working mode of the transfer line and we defined additional

requirements to designs of magnetic elements and power supplies.

Transfer of bunches from Injection Complex to BEP was a lot of work. We synchronized RF systems of Injection Complex and VEPP-2000 facility. The control of power supplies and beam diagnostics are debugged. We written software applications. The bunch is transported through all turns.

The transfer line will allow us to obtain new data on detectors SND [13] and CMD-3 [14].

## ACKNOWLEDGMENT

Thanks to L.N. Arapov, D.B. Burenkov, I.N. Churkin, K.V. Dyakov, Yu.I. Koysin, I.E. Korenev, N.N. Lebedev, E.B. Levichev, P.V. Logatchev, S.A. Mishin, M.I. Nepomnyaschykh, A.A. Novikov, A.V. Polyansky, R.Z. Pronik, O.A. Proskurina, A.L. Romanov, S.I. Ruvinsky, S.V. Seleznev, L.E. Serdakov, A.N. Skrinsky, V.P. Cherepanov, V.A. Shishkin, G.G. Shumakov, V.D. Yudin, V.K. Zhurba.

## REFERENCES

- [1] Yu.A. Rogovsky et al., "Status and perspectives of the VEPP-2000 complex," Proc. of RuPAC2014, Obninsk, Kaluga Region, Russia.
- [2] A.V. Akimov et al., "Status of Injection Complex VEPP-5: machine commissioning and first experience of positron storage," Proc. of IPAC2014, Dresden, Germany.
- [3] D. Berkaev et al., "Commissioning of upgraded VEPP-2000 injection chain," Proc. of IPAC2016, Busan, Korea.
- [4] I.M. Zemlyansky et al., "Electron and positron beams transportation channels to BINP colliders," Proc. of RuPAC2014, Obninsk, Kaluga Region, Russia.
- [5] A.P. Lysenko et al., "Program of numerical simulation of accelerator structures RING," BINP, Novosibirsk, Russia.
- [6] A.N. Dubrovin, "Program of magnetic calculations MERMAID," BINP, Novosibirsk, Russia.
- [7] V.V. Rashchenko, "A ГИД-25 Bipolar Pulse Generator for Energizing Elements of the K500 Beam Transportation Channel," Instrum. Exp. Tech., 2012, Vol. 55, No. 1, pp. 49–55.
- [8] A. Senchenko et al., "VEPP-2000 collider control system," Proceedings of PCaPAC2012, Kolkata, India.
- [9] D. Bolkhovityanov, "CXv4, a modular control system," Proceedings of ICALEPCS2015, Melbourne, Australia.
- [10] A. Pavlenko, "Electronics for precise measurements of accelerator pulsed magnets," Proc. of IPAC2013, Shanghai, China.
- [11] A.M. Batrakov et al., "Precision Digital Signal Integrators with Accurate Synchronization," Optoelectron. Instrument. Proc., 2015, Vol. 51, No. 1, pp. 51–57.
- [12] D. Shwartz et al., "Booster of electrons and positrons (BEP) upgrade to 1 GeV," Proc. of IPAC2014, Dresden, Germany.
- [13] M.N. Achasov et al., "Search for the  $\eta' \rightarrow e^+e^-$  decay with the SND detector," Phys. Rev. D, 2015, Vol. 91, Iss. 9.
- [14] D.N. Shemyakin et al., "Measurement of the  $e^+e^- \rightarrow K^+K^-\pi^+\pi^-$  cross section with the CMD-3 detector at the VEPP-2000 collider," Phys. Lett. B, 2016, Vol. 756, pp. 153–160.